

型号 Model	轴流式 通风机号 Tube Fan No.	进线 进线号 Inlet Fan No.	轴流式 通风机号 Tube Fan No.	电压 交流电压 VAC	频率 频率 Hz	风量 风量 CFM	噪音 噪音 dB	功率 功率 Watts	速度 速度 RPM	噪音水平 Noise level dB	工作温度 Operating Temperature °C
-------------	-----------------------------	----------------------------	-----------------------------	-------------------	----------------	-----------------	----------------	-------------------	-----------------	---------------------------	--

172X150X50mm

SP100A	11505BRL		Sleeve	115	50/60	190/230	0.50/0.48	46/42	2700/3100	58/63	0°~+70°C
	11505BRL		Ball	115	50/60	200/240	0.50/0.48	46/46	2700/3100	58/63	-20°~+86°C
DP100A	21505BRL		Sleeve	220/240	50/60	190/230	0.25/0.23	46/40	2700/3100	58/63	0°~+70°C
	21505BRL		Ball	220/240	50/60	200/240	0.25/0.23	46/40	2700/3100	58/63	-20°~+86°C

120X120X38mm

SP100A	11205ST	11205SL	Sleeve	115	50/60	95/115	0.27/0.24	22/20	2700/3100	44/49	0°~+70°C
	11205BT	11205BL	Ball	115	50	95/115	0.27/0.24	22/20	2700/3100	44/49	-20°~+86°C
DP100A	21205ST	21205SL	Sleeve	220/240	50	95/115	0.13/0.12	22/21	2700/3100	44/49	0°~+70°C
	21205BT	21205BL	Ball	220/240	50	95/115	0.13/0.12	22/21	2700/3100	44/49	-20°~+86°C
SP101A	11234ST	11234SL	Sleeve	115	50	85/105	0.21/0.19	20/18	2550/2900	43/48	0°~+70°C
	11234BT	11234BL	Ball	115	50	85/105	0.21/0.19	20/18	2550/2900	43/48	-20°~+86°C
DP101A	21234ST	21234SL	Sleeve	220/240	50	85/105	0.12/0.11	20/19	2550/2900	43/48	0°~70°C
	21234BT	21234BL	Ball	220/240	50	85/105	0.12/0.11	20/19	2550/2900	43/48	-20°~+86°C

120X120X25mm

SP101AT	1122HST	1122HSL	Sleeve	115	50/60	65/76	0.20/0.19	17/15	2100/2300	38/42	0°~+70°C
	1122HBT	1122HBL	Ball	115	50/60	65/76	0.20/0.19	17/15	2100/2300	38/42	-20°~+86°C
DP101AT	1122HST	1122HSL	Sleeve	220/240	50/60	65/76	0.10/0.09	17/15	2100/2300	38/42	0°~+70°C
	1122HBT	1122HBL	Ball	220/240	50/60	65/76	0.10/0.09	17/15	2100/2300	38/42	-20°~+86°C

92X92X25mm

SF1500A	1092HST	1092HSL	Sleeve	115	50/60	29/36	0.12/0.11	13/12	2250/2700	35/39	0°~+70°C
	1092HBT	1092HBL	Ball	115	50/60	29/36	0.12/0.11	13/12	2250/2700	35/39	-20°~+86°C
SF2000A	1092HST	2092HSL	Sleeve	220/240	50/60	29/36	0.07/0.06	14.5/14	2250/2700	35/39	0°~+70°C
	1092HBT	2092HBL	Ball	220/240	50/60	29/36	0.07/0.06	14.5/14	2250/2700	35/39	-20°~+86°C

80X80X38mm

SF1500A	1083HSL		Sleeve	115	50/60	23/30	0.15/0.13	14/12	2300/2750	31/35	0°~+70°C
	1083HBL		Ball	115	50/60	23/30	0.15/0.13	14/12	2300/2750	31/35	-20°~+86°C
SF2000A	2083HSL		Sleeve	220/240	50/60	23/30	0.07/0.07	14/13.5	2300/2750	31/35	0°~+70°C
	2083HBL		Ball	220/240	50/60	23/30	0.07/0.07	14/13.5	2300/2750	31/35	-20°~+86°C

80X80X25mm

SF1500AT	1082HSL		Sleeve	115	50/60	17/21	0.12/0.11	12/11	2350/2800	29/33	0°~+70°C
	1082HBL		Ball	115	50/60	17/21	0.12/0.11	12/11	2350/2800	29/33	-20°~+86°C
SF2000AT	2082HSL		Sleeve	220/240	50/60	17/21	0.07/0.07	14/13.5	2350/2800	29/33	0°~+70°C
	2082HBL		Ball	220/240	50/60	17/21	0.07/0.07	14/13.5	2350/2800	29/33	-20°~+86°C

172X150X50mm




115V,220/240VAC
3100RPM 230CFM
2700RPM 190CFM
Aluminum Frame



120X120X38mm




115V,220/240AC
3100RPM 115CFM
2900RPM 105CFM
Aluminum Frame



120X120X25mm




115V,220/240VAC
2500RPM 77CFM
2200RPM 62CFM
Aluminum Frme






92X92X25mm

115V,220/240VAC
2700RPM 36CFM
2200RPM 26CFM
Aluminum Frame




80X80X38mm

115V,220/240VAC
2750RPM 30CFM
2500RPM 23CFM
Aluminum Frame



80X80X25mm

115V,200/240VAC
2800RPM 21CFM
2300RPM 15CFM
Aluminum Frame



防护网 WIREFORM FINGER GUARD



无刷式直流电风机 BRUSHLESS DC FANS

型号 Model 料号 Number	扇 Beering BR System	电压 Voltage 交流/直流 VAC	风量 Air Volume AIR Flow CFM	电流 Current SIC AMP	功率 Power AC/DC Watts	转速 Speed 每分钟转速 RPM	噪音水平 Noise level dBA	工作温度 Operating Model Temperature °C	
120X120X38mm									
12038HD1BPL	Ball	12V		0.50		3000	46	-10°~+70°C	
12038HD1SPL	Sleeve	12V		0.50		3000	46	0°~+70°C	
12038HD2BPL	Ball	24V		0.30		3000	46	-10°~+70°C	
12038HD2SPL	Sleeve	24V		0.30		3000	46	0°~+70°C	
12038MD1BPL	Ball	12V		0.38		2600	40	-10°~+70°C	
12038MD1SPL	Sleeve	12V		0.38		2600	40	0°~+70°C	
12038MD2BPL	Ball	24V		0.20		2600	40	-10°~+70°C	
12038MD2SPL	Sleeve	24V		0.20		2600	40	0°~+70°C	
120X120X25mm									
12025HD1BPL	Ball	12V		0.38		3000	42	-10°~+70°C	
12025HD1SPL	Sleeve	12V		0.38		3000	42	0°~+70°C	
12025HD1BPL	Ball	24V		0.20		3000	42	-10°~+70°C	
12025HD2SPL	Sleeve	24V		0.20		3000	42	0°~+70°C	
12025MD1BPL	Ball	12V		0.30		2600	38	-10°~+70°C	
12025MD1SPL	Sleeve	12V		0.30		2600	38	0°~+70°C	
12025MD2BPL	Ball	24V		0.16		2600	38	-10°~+70°C	
12025MD2SPL	Sleeve	24V		0.16		2600	38	0°~+70°C	
92X92X25mm									
KD1209PTS1	Sleeve	12	49	83	0.23	2.8	3200	53	0°~+70°C
KD1209PTB1	Ball	12	51.5	87.3	0.23	2.8	3400	34.5	-10°~+70°C
KD1209PTS2	Sleeve	12	43.5	73.7	0.17	2.1	2700	27.5	0°~+70°C
KD1209PTB2	Ball	12	46	80	0.17	2.1	2800	30	-10°~+70°C
KD1209PTS3	Sleeve	12	41	69.5	0.13	1.6	2400	25.8	0°~+70°C
KD1209PTB3	Ball	12	43	72.9	0.13	1.6	2600	27	-10°~+70°C
KD2409PTS1	Sleeve	24	49	83	0.16	3.8	3200	34	0°~+70°C
KD2409PTB1	Ball	24	51.5	87.3	0.16	3.8	3400	34.5	-10°~+70°C
KD2409PTS2	Sleeve	24	43.5	73.7	0.10	2.4	2700	27.5	0°~+70°C
KD2409PTB2	Ball	24	46	80	0.10	2.4	2800	30	-10°~+70°C
KD2409PTS3	Sleeve	24	41	69.5	0.08	1.9	2400	25.8	0°~+70°C
KD2409PTB3	Ball	24	43	72.9	0.08	1.9	2600	27	-10°~+70°C
80X80X25mm									
KD1208PTS1	Sleeve	12	36	61	0.23	2.8	3000	34	0°~+70°C
KD1208PTB1	Ball	12	37.5	63.5	0.23	2.8	3200	36	-10°~+70°C
KD1208PTS2	Sleeve	12	32.5	55	0.17	2.1	2650	29	0°~+70°C
KD1208PTB2	Ball	12	33	56	0.17	2.1	2800	30	-10°~+70°C
KD1208PTS3	Sleeve	12	26	44	0.13	1.6	2300	25	0°~+70°C
KD1208PTB3	Ball	12	27.5	46.6	0.13	1.6	2450	27	-10°~+70°C
KD2408PTS1	Sleeve	24	36	61	0.17	4.1	3000	34	0°~+70°C
KD2408PTB1	Ball	24	37.5	63.5	0.17	4.1	3200	36	-10°~+70°C
KD2408PTS2	Sleeve	24	32.5	55	0.11	2.6	2650	29	0°~+70°C
KD2408PTB2	Ball	24	33	56	0.11	2.6	2800	30	-10°~+70°C
KD2408PTS3	Sleeve	24	26	44	0.10	2.4	2300	25	0°~+70°C
KD2408PTB3	Ball	24	27.5	46.6	0.10	2.4	2450	27	-10°~+70°C
60X60X25mm									
KD1206PTS1	Sleeve	12	21.7	36.8	0.19	2.3	4500	34	0°~+70°C
KD1206PTB1	Sleeve	12	17.6	29.8	0.16	1.9	3800	31	0°~+70°C
KD1206PTS2	Sleeve	12	15.9	27	0.09	1.1	3300	26.7	0°~+70°C
KD2406PTS1	Sleeve	24	21.7	36.8	0.12	2.8	4500	34	0°~+70°C
KD2406PTB1	Sleeve	24	17.6	29.8	0.08	1.9	3800	31	0°~+70°C
KD2406PTS2	Sleeve	24	15.9	27	0.07	1.6	3300	26.7	0°~+70°C
50X50X10mm									
KD1205SPS2	Sleeve	12	17.8	30.2	0.16	1.9	4000	31	0°~+70°C
KD1205SPS3	Sleeve	12	14.8	25.1	0.09	1.1	2300	26	0°~+70°C
KD0505SPS2	Sleeve	05	17.8	30.2	0.38	1.9	4000	31	0°~+70°C
KD0505SPS3	Sleeve	05	14.8	25.1	0.24	1.2	3300	26	0°~+70°C
40X40X10mm									
KD1204PPS2	Sleeve	12	6.3	10.7	0.06	0.8	5500	24.3	0°~+70°C
KD0504PPS2	SLEEVE	05	6.3	10.7	0.16	0.8	5500	24.3	0°~+70°C



120x120x38mm
 .3100RPM-108CFM
 .2800RPM-98CFM
 .2400RPM-84CFM
 .5.12 and 24 VDC
 .PBT plastic,94V-0
 .Sleeve & Ball Bearing



120x120x25mm
 .3100RPM-90CFM
 .2800RPM-80CFM
 .2400RPM-69CFM
 .5.12 and 24 VDC
 .PBT plastic,94V-0
 .Sleeve & Ball Bearing



92x92x25mm
 .3200RPM-50CFM
 .2800RPM-44CFM
 .2400RPM-42CFM
 .5.12 and 24 VDC
 .PBT plastic,94V-0
 .Sleeve & Ball Bearing



80x80x25mm
 .3000RPM-41.7CFM
 .2650RPM-34.4CFM
 .2200RPM-29.4CFM
 .5.12 and 24VDC
 .PBT plastic,94V-0
 .Sleeve & Ball bearing



60x60x25mm
 .4000RPM-17.8CFM
 .3300RPM-14.8CFM
 .5.12 and 24 VDC
 .PBT plastic,94V-0
 .Sleeve & Ball bearing



50X50X10mm
 .5100RPM-9.6CFM
 .4300RPM-8.0CFM
 .3500RPM-7.0CFM
 .5 and 12 VDC
 .PBT plastic,94V-0
 .Sleeve & Ball Bearing