



LOUD SPEAKER




Type	YD40-1
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.25 (0.5)
Resonance Frequency (Hz)	430±20%
Rated Freq. Range (Hz)	5-2000
Sound Pressure Level (dB)	80±3
Magnet (g)	11
Operating Temperature (°C)	-10~+40




Type	YD40-11
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.4)
Resonance Frequency (Hz)	650±20%
Rated Freq. Range (Hz)	5-2500
Sound Pressure Level (dB)	80±3
Magnet (g)	11.0
Operating Temperature (°C)	-10~+40



Type	YD40-12
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.25 (0.5)
Resonance Frequency (Hz)	460±20%
Rated Freq. Range (Hz)	5-4000
Sound Pressure Level (dB)	80±3
Magnet (g)	1.0
Operating Temperature (°C)	-10~+40




Type	YD40-13
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	700±20%
Rated Freq. Range (Hz)	5-5000
Sound Pressure Level (dB)	80±3
Magnet (g)	5.5
Operating Temperature (°C)	-10~+40




LOUD SPEAKER




Type	YD45-1
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.2@)
Resonance Frequency (Hz)	450±20%
Rated Freq. Range (Hz)	1-4000
Sound Pressure Level (dB)	85±3
Magnet (g)	15.6
Operating Temperature (°C)	-10~+40




Type	YD45-51
Rated Impedance (Ω)	45±15%
Rated (Max.) Power (W)	0.25 (0.4)
Resonance Frequency (Hz)	700±20%
Rated Freq. Range (Hz)	1-2500
Sound Pressure Level (dB)	85±2
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40



Type	YD45-13(P40)
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.25 (0.8)
Resonance Frequency (Hz)	600±20%
Rated Freq. Range (Hz)	1-4000
Sound Pressure Level (dB)	85±3
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40




Type	YD50-1
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.2 (0.4)
Resonance Frequency (Hz)	380
Rated Freq. Range (Hz)	1-3000
Sound Pressure Level (dB)	85
Magnet (g)	15.6
Operating Temperature (°C)	10~+40




LOUD SPEAKER




Type	YD55-1B
Rated Impedance (Ω)	28 \pm 15%
Rated (Max.) Power (W)	0.2 (0.4)
Resonance Frequency (Hz)	550 \pm 20%
Rated Freq. Range (Hz)	1-4500
Sound Pressure Level (dB)	84 \pm 2
Magnet (g)	16.5
Operating Temperature ($^{\circ}$ C)	-10-+40




Type	YD55-2
Rated Impedance (Ω)	8 \pm 20%
Rated (Max.) Power (W)	0.2 (0.2)
Resonance Frequency (Hz)	450 \pm 20%
Rated Freq. Range (Hz)	1-4000
Sound Pressure Level (dB)	84 \pm 3
Magnet (g)	15.5
Operating Temperature ($^{\circ}$ C)	-10-+40



Type	YD56-3
Rated Impedance (Ω)	16 \pm 15%
Rated (Max.) Power (W)	0.2 (0.4)
Resonance Frequency (Hz)	380 \pm 20%
Rated Freq. Range (Hz)	1-4500
Sound Pressure Level (dB)	85 \pm 3
Magnet (g)	17.3
Operating Temperature ($^{\circ}$ C)	-10-+40




Type	YD56-4
Rated Impedance (Ω)	32 \pm 15%
Rated (Max.) Power (W)	0.4 (0.5)
Resonance Frequency (Hz)	370 \pm 20%
Rated Freq. Range (Hz)	1-4000
Sound Pressure Level (dB)	85 \pm 3 \pm 2
Magnet (g)	17.3
Operating Temperature ($^{\circ}$ C)	-10-+40




LOUD SPEAKER




Type	YD56-7
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.5 (1)
Resonance Frequency (Hz)	360±5
Rated Freq. Range (Hz)	5~3430
Sound Pressure Level (dB)	≥83
Magnet (g)	17.2
Operating Temperature (°C)	-10~+40




Type	YD56-9
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.5 (1)
Resonance Frequency (Hz)	270±20%
Rated Freq. Range (Hz)	5~5000
Sound Pressure Level (dB)	82±3
Magnet (g)	27.5
Operating Temperature (°C)	-10~+40



Type	YD56-11
Rated Impedance (Ω)	50±20%
Rated (Max.) Power (W)	0.25 (0.4)
Resonance Frequency (Hz)	420±20%
Rated Freq. Range (Hz)	5~3500
Sound Pressure Level (dB)	85±3
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40




Type	YD56-11B
Rated Impedance (Ω)	25±20%
Rated (Max.) Power (W)	0.25 (0.4)
Resonance Frequency (Hz)	550±20%
Rated Freq. Range (Hz)	5~4000
Sound Pressure Level (dB)	83±3
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40




LOUD SPEAKER




Type	YD50-20
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.5 (1)
Resonance Frequency (Hz)	300±20%
Rated Freq. Range (Hz)	5-4000
Sound Pressure Level (dB)	85±3
Magnet (g)	2.5
Operating Temperature (°C)	-10~+40




Type	YD58-1
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.3 (0.6)
Resonance Frequency (Hz)	400±20%
Rated Freq. Range (Hz)	1-3500
Sound Pressure Level (dB)	85±3
Magnet (g)	18.8
Operating Temperature (°C)	-10~+40



Type	YD58-1B
Rated Impedance (Ω)	25±15%
Rated (Max.) Power (W)	0.3 (0.6)
Resonance Frequency (Hz)	400±20%
Rated Freq. Range (Hz)	1-3500
Sound Pressure Level (dB)	85±3
Magnet (g)	18.8
Operating Temperature (°C)	-10~+40



Type	YD58-3
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.2 (0.6)
Resonance Frequency (Hz)	400±20%
Rated Freq. Range (Hz)	1-3400
Sound Pressure Level (dB)	85±3
Magnet (g)	17.3
Operating Temperature (°C)	-10~+40




LOUD SPEAKER




Type
Rated Impedance (Ω)
Rated (Max.) Power (W)
Resonance Frequency (Hz)
Rated Freq. Range (Hz)
Sound Pressure Level (dB)
Magnet (g)
Operating Temperature (°C)

YD55-2B
 8Ω±20%
 0.3 (0.5)
 800±20%
 1-3400
 87±2
 17.5
 -10~+40




Type
Rated Impedance (Ω)
Rated (Max.) Power (W)
Resonance Frequency (Hz)
Rated Freq. Range (Hz)
Sound Pressure Level (dB)
Magnet (g)
Operating Temperature (°C)

YD55-4
 8Ω±15%
 0.3 (0.5)
 400±20%
 1-3500
 85±3
 16.8
 -10~+40




Type
Rated Impedance (Ω)
Rated (Max.) Power (W)
Resonance Frequency (Hz)
Rated Freq. Range (Hz)
Sound Pressure Level (dB)
Magnet (g)
Operating Temperature (°C)

YD55-11
 8Ω±20%
 0.25 (0.5)
 400±20%
 1-3500
 85±2
 1.8
 -10~+40




Type
Rated Impedance (Ω)
Rated (Max.) Power (W)
Resonance Frequency (Hz)
Rated Freq. Range (Hz)
Sound Pressure Level (dB)
Magnet (g)
Operating Temperature (°C)

YD55-12
 8Ω±15%
 0.25 (0.4)
 450±20%
 1-3500
 85±3
 1.8
 -10~+40




LOUD SPEAKER


Type YD58-13(N4)
Rated Impedance (Ω) 8±15%
Rated (Max.) Power (W) 0.25 (0.5)
Resonance Frequency (Hz) 450±20%
Rated Freq. Range (Hz) 5-4000
Sound Pressure Level (dB) 85±3
Magnet (g) 1.8
Operating Temperature (°C) -10~+40




Type YD58-16(N4)
Rated Impedance (Ω) 8±15%
Rated (Max.) Power (W) 0.25 (0.5)
Resonance Frequency (Hz) 450±20%
Rated Freq. Range (Hz) 5-4000
Sound Pressure Level (dB) 85±3
Magnet (g) 1.8
Operating Temperature (°C) -10~+40



Type YD58-18(N4)
Rated Impedance (Ω) 8±15%
Rated (Max.) Power (W) 0.25 (0.5)
Resonance Frequency (Hz) 550±50
Rated Freq. Range (Hz) 5-5500
Sound Pressure Level (dB) 87±3
Magnet (g) 1.8
Operating Temperature (°C) -10~+40




Type YD64-11
Rated Impedance (Ω) 50±15%
Rated (Max.) Power (W) 0.5 (1)
Resonance Frequency (Hz) 500±20
Rated Freq. Range (Hz) 5-3400
Sound Pressure Level (dB) 88±2
Magnet (g) 2.5
Operating Temperature (°C) -10~+40




LOUD SPEAKER




Type	YD60-1
Rated Impedance (Ω)	8±10%
Rated (Max.) Power (W)	1 (2)
Resonance Frequency (Hz)	280±20%
Rated Freq. Range (Hz)	1~2000
Sound Pressure Level (dB)	85±3
Magnet (g)	17.8
Operating Temperature (°C)	-10~+40




Type	YD60-2
Rated Impedance (Ω)	8±10%
Rated (Max.) Power (W)	0.5 (1)
Resonance Frequency (Hz)	350±20%
Rated Freq. Range (Hz)	1~2000
Sound Pressure Level (dB)	85±3
Magnet (g)	16.6
Operating Temperature (°C)	-10~+40



Type	YD60-3
Rated Impedance (Ω)	8±10%
Rated (Max.) Power (W)	2 (3)
Resonance Frequency (Hz)	320±20%
Rated Freq. Range (Hz)	1~2000
Sound Pressure Level (dB)	85±3
Magnet (g)	16.6
Operating Temperature (°C)	-10~+40




Type	YD60-6
Rated Impedance (Ω)	4±10%
Rated (Max.) Power (W)	5 (7)
Resonance Frequency (Hz)	230±20%
Rated Freq. Range (Hz)	1~10000
Sound Pressure Level (dB)	88±2
Magnet (g)	63
Operating Temperature (°C)	-25~+50




LOUD SPEAKER


Type	YD88-8
Rated Impedance (Ω)	16±15%
Rated (Max.) Power (W)	1 (2)
Resonance Frequency (Hz)	350±20%
Rated Freq. Range (Hz)	1-4000
Sound Pressure Level (dB)	85±2
Magnet (g)	16.5
Operating Temperature (°C)	-10~+40




Type	YD88-11
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	1 (2)
Resonance Frequency (Hz)	350±20%
Rated Freq. Range (Hz)	1-3500
Sound Pressure Level (dB)	85±3
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40



Type	YD88-13(N)
Rated Impedance (Ω)	50±15%
Rated (Max.) Power (W)	0.2 (0.2)
Resonance Frequency (Hz)	350±20%
Rated Freq. Range (Hz)	1-2500
Sound Pressure Level (dB)	84±2
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40




Type	YD88-15(N)
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.25 (0.5)
Resonance Frequency (Hz)	300±20%
Rated Freq. Range (Hz)	1-4000
Sound Pressure Level (dB)	88±3
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40




LOUD SPEAKER


Type	YD88-8
Rated Impedance (Ω)	16±15%
Rated (Max.) Power (W)	1 (2)
Resonance Frequency (Hz)	250±20%
Rated Freq. Range (Hz)	1-4000
Sound Pressure Level (dB)	85±2
Magnet (g)	14.5
Operating Temperature (°C)	-10~+40



Type	YD88-11
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	1 (2)
Resonance Frequency (Hz)	250±20%
Rated Freq. Range (Hz)	1-2500
Sound Pressure Level (dB)	85±3
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40



Type	YD88-12(N)
Rated Impedance (Ω)	50±15%
Rated (Max.) Power (W)	0.2 (0.2)
Resonance Frequency (Hz)	250±20%
Rated Freq. Range (Hz)	1-2500
Sound Pressure Level (dB)	84±2
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40



Type	YD88-15(N)
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.25 (0.5)
Resonance Frequency (Hz)	300±20%
Rated Freq. Range (Hz)	1-4000
Sound Pressure Level (dB)	88±3
Magnet (g)	1.8
Operating Temperature (°C)	-10~+40

