





LOUD SPEAKER





| | |
|---------------------------------------|----------------------|
| Type | YD66-16 |
| Rated Impedance (Ω) | 8 \pm 15% |
| Rated (Max.) Power (W) | 0.5 (1) |
| Resonance Frequency (Hz) | 350 \pm 15% |
| Rated Freq. Range (Hz) | f _s -5000 |
| Sound Pressure Level (dB) | 85 \pm 3 |
| Magnet (g) | 1.8 |
| Operating Temperature ($^{\circ}$ C) | -10~+40 |





| | |
|---------------------------------------|----------------------|
| Type | YD70-11 |
| Rated Impedance (Ω) | 25 \pm 15% |
| Rated (Max.) Power (W) | 0.5 (1) |
| Resonance Frequency (Hz) | 260 \pm 20% |
| Rated Freq. Range (Hz) | f _s -5000 |
| Sound Pressure Level (dB) | 85 \pm 3 |
| Magnet (g) | 1.8 |
| Operating Temperature ($^{\circ}$ C) | -10~+40 |



| | |
|---------------------------------------|----------------------|
| Type | YD70-11B |
| Rated Impedance (Ω) | 50 \pm 15% |
| Rated (Max.) Power (W) | 0.5 (1) |
| Resonance Frequency (Hz) | 400 \pm 20% |
| Rated Freq. Range (Hz) | f _s -5000 |
| Sound Pressure Level (dB) | 85 \pm 2 |
| Magnet (g) | 1.8 |
| Operating Temperature ($^{\circ}$ C) | -10~+40 |





| | |
|---------------------------------------|----------------------|
| Type | YD70-12B(Nd) |
| Rated Impedance (Ω) | 8 \pm 15% |
| Rated (Max.) Power (W) | 0.5 (1) |
| Resonance Frequency (Hz) | 400 \pm 20% |
| Rated Freq. Range (Hz) | f _s -5000 |
| Sound Pressure Level (dB) | 85 \pm 2 |
| Magnet (g) | 1.8 |
| Operating Temperature ($^{\circ}$ C) | -10~+40 |





LOUD SPEAKER





| | |
|--|-----------------|
| Type | YD78-1 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 0.5 (1) |
| Resonance Frequency (Hz) | $260 \pm 20\%$ |
| Rated Freq. Range (Hz) | $f_c \sim 5000$ |
| Sound Pressure Level (dB) | 86 ± 2 |
| Magnet (g) | 16.6 |
| Operating Temperature ($^{\circ}\text{C}$) | $-10 \sim +40$ |





| | |
|--|------------------|
| Type | YD78-2 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 0.5 (1) |
| Resonance Frequency (Hz) | $230 \pm 20\%$ |
| Rated Freq. Range (Hz) | $f_c \sim 15000$ |
| Sound Pressure Level (dB) | 87 ± 3 |
| Magnet (g) | 17.3 |
| Operating Temperature ($^{\circ}\text{C}$) | $-10 \sim +40$ |



| | |
|--|------------------|
| Type | YD78-6 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 3 (5) |
| Resonance Frequency (Hz) | 170 ± 30 |
| Rated Freq. Range (Hz) | $f_c \sim 15000$ |
| Sound Pressure Level (dB) | 87 ± 3 |
| Magnet (g) | 52 |
| Operating Temperature ($^{\circ}\text{C}$) | $-10 \sim +40$ |





| | |
|--|------------------|
| Type | YD78-8 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 3 (5) |
| Resonance Frequency (Hz) | $230 \pm 20\%$ |
| Rated Freq. Range (Hz) | $f_c \sim 15000$ |
| Sound Pressure Level (dB) | 87 ± 2 |
| Magnet (g) | 52 |
| Operating Temperature ($^{\circ}\text{C}$) | $-10 \sim +40$ |





LOUD SPEAKER





| | |
|--|----------------|
| Type | YD78-11 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 0.5 (1) |
| Resonance Frequency (Hz) | $260 \pm 20\%$ |
| Rated Freq. Range (Hz) | f-5000 |
| Sound Pressure Level (dB) | 87 ± 2 |
| Magnet (g) | 2.5 |
| Operating Temperature ($^{\circ}\text{C}$) | -10~+40 |





| | |
|--|----------------|
| Type | YD78-13 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 1 (1.5) |
| Resonance Frequency (Hz) | $260 \pm 20\%$ |
| Rated Freq. Range (Hz) | f-12000 |
| Sound Pressure Level (dB) | 83 ± 2 |
| Magnet (g) | 2.5 |
| Operating Temperature ($^{\circ}\text{C}$) | -10~+40 |



| | |
|--|----------------|
| Type | YD78-15 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 2 (3) |
| Resonance Frequency (Hz) | $250 \pm 15\%$ |
| Rated Freq. Range (Hz) | f-5000 |
| Sound Pressure Level (dB) | 85 ± 3 |
| Magnet (g) | 33 |
| Operating Temperature ($^{\circ}\text{C}$) | -10~+40 |





| | |
|--|----------------|
| Type | YD93-11 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 3 (5) |
| Resonance Frequency (Hz) | $180 \pm 20\%$ |
| Rated Freq. Range (Hz) | f-15000 |
| Sound Pressure Level (dB) | 87 ± 2 |
| Magnet (g) | 86 |
| Operating Temperature ($^{\circ}\text{C}$) | -10~+40 |





LOUD SPEAKER





Type YD100-1
 Rated Impedance (Ω) $8 \pm 15\%$
 Rated (Max.) Power (W) 1 (2)
 Resonance Frequency (Hz) $180 \pm 15\%$
 Rated Freq. Range (Hz) $f_0 \sim 4000$
 Sound Pressure Level (dB) 88 ± 3
 Magnet (g) 51
 Operating Temperature ($^{\circ}\text{C}$) $-10 \sim +40$





Type YD100-3
 Rated Impedance (Ω) $8 \pm 15\%$
 Rated (Max.) Power (W) 3 (5)
 Resonance Frequency (Hz) $150 \pm 20\%$
 Rated Freq. Range (Hz) $f_0 \sim 8000$
 Sound Pressure Level (dB) 90 ± 3
 Magnet (g) 51
 Operating Temperature ($^{\circ}\text{C}$) $-10 \sim +40$



Type YD200-1
 Rated Impedance (Ω) $8 \pm 15\%$
 Rated (Max.) Power (W) 20 (30)
 Resonance Frequency (Hz) $45 \pm 15\%$
 Rated Freq. Range (Hz) $f_0 \sim 5000$
 Sound Pressure Level (dB) 93 ± 3
 Magnet (g) 400
 Operating Temperature ($^{\circ}\text{C}$) $-10 \sim +40$





Type YDP2035-11
 Rated Impedance (Ω) $8 \pm 15\%$
 Rated (Max.) Power (W) 1 (2)
 Resonance Frequency (Hz) $600 \pm 20\%$
 Rated Freq. Range (Hz) $f_0 \sim 5000$
 Sound Pressure Level (dB) 75 ± 3
 Magnet (g) 1.1
 Operating Temperature ($^{\circ}\text{C}$) $-10 \sim +40$





LOUD SPEAKER





| | |
|--|-------------------|
| Type | YDP2040-11 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 1 (2) |
| Resonance Frequency (Hz) | $450 \pm 20\%$ |
| Rated Freq. Range (Hz) | f-5000 |
| Sound Pressure Level (dB) | 78 \pm 3 |
| Magnet (g) | 1.1 |
| Operating Temperature ($^{\circ}\text{C}$) | -10~+40 |





| | |
|--|-------------------|
| Type | YDP3040-11 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 1 (2) |
| Resonance Frequency (Hz) | $450 \pm 20\%$ |
| Rated Freq. Range (Hz) | f-12000 |
| Sound Pressure Level (dB) | 78 \pm 3 |
| Magnet (g) | 1.8 |
| Operating Temperature ($^{\circ}\text{C}$) | -10~+40 |



| | |
|--|-------------------|
| Type | YDP4070-11 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 2 (5) |
| Resonance Frequency (Hz) | $300 \pm 20\%$ |
| Rated Freq. Range (Hz) | f-20000 |
| Sound Pressure Level (dB) | 83 \pm 3 |
| Magnet (g) | 1.8 |
| Operating Temperature ($^{\circ}\text{C}$) | -10~+40 |





| | |
|--|-------------------|
| Type | YDP4070-12 |
| Rated Impedance (Ω) | $8 \pm 15\%$ |
| Rated (Max.) Power (W) | 2 (5) |
| Resonance Frequency (Hz) | $300 \pm 20\%$ |
| Rated Freq. Range (Hz) | f-20000 |
| Sound Pressure Level (dB) | 82 \pm 2 |
| Magnet (g) | 33 |
| Operating Temperature ($^{\circ}\text{C}$) | -10~+40 |





LOUD SPEAKER





Type YDP5090-1
 Rated Impedance (Ω) $8 \pm 15\%$
 Rated (Max.) Power (W) 3 (5)
 Resonance Frequency (Hz) $200 \pm 20\%$
 Rated Freq. Range (Hz) $f \sim 12000$
 Sound Pressure Level (dB) 88 ± 3
 Magnet (g) 53
 Operating Temperature ($^{\circ}\text{C}$) $-10 \sim +40$



Type YDP5090-3
 Rated Impedance (Ω) $4 \pm 15\%$
 Rated (Max.) Power (W) 3 (5)
 Resonance Frequency (Hz) $250 \pm 20\%$
 Rated Freq. Range (Hz) $f \sim 18000$
 Sound Pressure Level (dB) 84 ± 2
 Magnet (g) 65
 Operating Temperature ($^{\circ}\text{C}$) $-10 \sim +40$



Type YDP5090-11
 Rated Impedance (Ω) $8 \pm 15\%$
 Rated (Max.) Power (W) 3 (5)
 Resonance Frequency (Hz) $200 \pm 20\%$
 Rated Freq. Range (Hz) $f \sim 18000$
 Sound Pressure Level (dB) 84 ± 2
 Magnet (g) 70
 Operating Temperature ($^{\circ}\text{C}$) $-10 \sim +40$



Type YDP5090-12
 Rated Impedance (Ω) $16 \pm 15\%$
 Rated (Max.) Power (W) 2 (3)
 Resonance Frequency (Hz) $200 \pm 20\%$
 Rated Freq. Range (Hz) $f \sim 20000$
 Sound Pressure Level (dB) 82 ± 2
 Magnet (g) 5.5
 Operating Temperature ($^{\circ}\text{C}$) $-10 \sim +40$

