



# MYLAR SPEAKER


Type	YDB18-11
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.1)
Resonance Frequency (Hz)	1700±20%
Rated Freq. Range (Hz)	1-5000
Sound Pressure Level (dB)	75±3 at 10cm 1.41V
Magnet (g)	0.6
Operating Temperature (°C)	-10~+40




Type	YDB18-11
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.1)
Resonance Frequency (Hz)	800±20%
Rated Freq. Range (Hz)	1-2500
Sound Pressure Level (dB)	70±3
Magnet (g)	0.6
Operating Temperature (°C)	-10~+40



Type	YDB18-11A
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.1)
Resonance Frequency (Hz)	800±20%
Rated Freq. Range (Hz)	1-2500
Sound Pressure Level (dB)	70±3
Magnet (g)	0.6
Operating Temperature (°C)	-10~+40




Type	YDB20-1
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	700±20%
Rated Freq. Range (Hz)	1-4500
Sound Pressure Level (dB)	75±3
Magnet (g)	3.7
Operating Temperature (°C)	-10~+40




# MYLAR SPEAKER




<b>Type</b>	<b>YDM00-11</b>
Rated Impedance (Ω)	32±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	1000±20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	75±3
Magnet (g)	2.8
Operating Temperature (°C)	-10~+40




<b>Type</b>	<b>YDM01-1</b>
Rated Impedance (Ω)	32±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	800±20%
Rated Freq. Range (Hz)	1-2500
Sound Pressure Level (dB)	70±3
Magnet (g)	2.8
Operating Temperature (°C)	-10~+40



<b>Type</b>	<b>YDM02-1</b>
Rated Impedance (Ω)	8±20%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	1000±20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	75±3
Magnet (g)	1
Operating Temperature (°C)	-10~+40




<b>Type</b>	<b>YDM03-2</b>
Rated Impedance (Ω)	25±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	800±20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	75±3
Magnet (g)	1
Operating Temperature (°C)	-10~+40




# MYLAR SPEAKER




**Type** Y0602-1  
**Rated Impedance (Ω)** 16±20%  
**Rated (Max.) Power (W)** 0.1 (0.2)  
**Resonance Frequency (Hz)** 500±20%  
**Rated Freq. Range (Hz)** 1-2000  
**Sound Pressure Level (dB)** 78±3  
**Magnet (g)** 3.7  
**Operating Temperature (°C)** -10~+40




**Type** Y0602-11  
**Rated Impedance (Ω)** 8±15%  
**Rated (Max.) Power (W)** 0.1 (0.2)  
**Resonance Frequency (Hz)** 500±20%  
**Rated Freq. Range (Hz)** 1-2000  
**Sound Pressure Level (dB)** 80±3  
**Magnet (g)** 1.1  
**Operating Temperature (°C)** -10~+40



**Type** Y0602-12  
**Rated Impedance (Ω)** 8±15%  
**Rated (Max.) Power (W)** 0.1 (0.2)  
**Resonance Frequency (Hz)** 500±20%  
**Rated Freq. Range (Hz)** 1-2000  
**Sound Pressure Level (dB)** 85±3  
**Magnet (g)** 3  
**Operating Temperature (°C)** -10~+40




**Type** Y0602-12A  
**Rated Impedance (Ω)** 8±15%  
**Rated (Max.) Power (W)** 0.1 (0.15)  
**Resonance Frequency (Hz)** 300±20%  
**Rated Freq. Range (Hz)** 1-2000  
**Sound Pressure Level (dB)** 85±3  
**Magnet (g)** 3  
**Operating Temperature (°C)** -10~+40




# MYLAR SPEAKER




Type	Y0602-1
Rated Impedance (Ω)	16±20%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	500±20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	78±3
Magnet (g)	3.7
Operating Temperature (°C)	-10~+40




Type	Y0602-11
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	500±20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	80±3
Magnet (g)	1.1
Operating Temperature (°C)	-10~+40



Type	Y0602-12
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	500±20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	85±3
Magnet (g)	3
Operating Temperature (°C)	-10~+40




Type	Y0602-12A
Rated Impedance (Ω)	8±15%
Rated (Max.) Power (W)	0.1 (0.15)
Resonance Frequency (Hz)	300±20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	85±3
Magnet (g)	3
Operating Temperature (°C)	-10~+40




# MYLAR SPEAKER




**Type** YO025-11  
**Rated Impedance (Ω)** 8±15%  
**Rated (Max.) Power (W)** 0.1 (0.2)  
**Resonance Frequency (Hz)** 700±20%  
**Rated Freq. Range (Hz)** 5-3500  
**Sound Pressure Level (dB)** 78±3  
**Magnet (g)** 0.5  
**Operating Temperature (°C)** -10-+40




**Type** YO025-12  
**Rated Impedance (Ω)** 8±15%  
**Rated (Max.) Power (W)** 0.1 (0.2)  
**Resonance Frequency (Hz)** 600±20%  
**Rated Freq. Range (Hz)** 5-5000  
**Sound Pressure Level (dB)** 80±3  
**Magnet (g)** 1.1  
**Operating Temperature (°C)** -10-+40



**Type** YO025-14  
**Rated Impedance (Ω)** 8±15%  
**Rated (Max.) Power (W)** 0.3 (0.6)  
**Resonance Frequency (Hz)** 520±20%  
**Rated Freq. Range (Hz)** 5-5000  
**Sound Pressure Level (dB)** 78±3  
**Magnet (g)** 0.5  
**Operating Temperature (°C)** -10-+40




**Type** YO025-1  
**Rated Impedance (Ω)** 8±20%  
**Rated (Max.) Power (W)** 0.1 (0.2)  
**Resonance Frequency (Hz)** 600±20%  
**Rated Freq. Range (Hz)** 5-3500  
**Sound Pressure Level (dB)** 78±3  
**Magnet (g)** 2.7  
**Operating Temperature (°C)** -10-+40




# MYLAR SPEAKER


<b>Type</b>	<b>YD808-3</b>
Rated Impedance ( $\Omega$ )	8±15%
Rated (Max.) Power (W)	0.15 (0.2)
Resonance Frequency (Hz)	100±20%
Rated Freq. Range (Hz)	5-2000
Sound Pressure Level (dB)	85±3
Magnet (g)	7
Operating Temperature (°C)	-10~+40




<b>Type</b>	<b>YD809-3</b>
Rated Impedance ( $\Omega$ )	8±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	600±20%
Rated Freq. Range (Hz)	5-2000
Sound Pressure Level (dB)	78±3
Magnet (g)	7
Operating Temperature (°C)	-10~+40



<b>Type</b>	<b>YD810-11</b>
Rated Impedance ( $\Omega$ )	16±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	550±20%
Rated Freq. Range (Hz)	5-2000
Sound Pressure Level (dB)	85±3
Magnet (g)	1.1
Operating Temperature (°C)	-10~+40




<b>Type</b>	<b>YD810-12</b>
Rated Impedance ( $\Omega$ )	16±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	550±20%
Rated Freq. Range (Hz)	5-2000
Sound Pressure Level (dB)	85±3
Magnet (g)	0.8
Operating Temperature (°C)	-10~+40




# MYLAR SPEAKER


<b>Type</b>	<b>YD808-3</b>
Rated Impedance ( $\Omega$ )	8±15%
Rated (Max.) Power (W)	0.15 (0.2)
Resonance Frequency (Hz)	100±20%
Rated Freq. Range (Hz)	5-2000
Sound Pressure Level (dB)	85±3
Magnet (g)	7
Operating Temperature (°C)	-10~+40




<b>Type</b>	<b>YD809-3</b>
Rated Impedance ( $\Omega$ )	8±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	600±20%
Rated Freq. Range (Hz)	5-2000
Sound Pressure Level (dB)	78±3
Magnet (g)	7
Operating Temperature (°C)	-10~+40



<b>Type</b>	<b>YD810-11</b>
Rated Impedance ( $\Omega$ )	16±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	550±20%
Rated Freq. Range (Hz)	5-2000
Sound Pressure Level (dB)	80±3
Magnet (g)	1.1
Operating Temperature (°C)	-10~+40




<b>Type</b>	<b>YD810-12</b>
Rated Impedance ( $\Omega$ )	16±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	550±20%
Rated Freq. Range (Hz)	5-2000
Sound Pressure Level (dB)	80±3
Magnet (g)	0.8
Operating Temperature (°C)	-10~+40



# MYLAR SPEAKER




**Type** Y0009-05  
**Rated Impedance (Ω)** 32±15%  
**Rated (Max.) Power (W)** 0.1 (0.15)  
**Resonance Frequency (Hz)** 600±20%  
**Rated Freq. Range (Hz)** 1-20000  
**Sound Pressure Level (dB)** 81±2  
**Magnet (g)** 1.1  
**Operating Temperature (°C)** -10~+40



Y0009-05




**Type** Y0008-1  
**Rated Impedance (Ω)** 8±15%  
**Rated (Max.) Power (W)** 0.15(0.3)  
**Resonance Frequency (Hz)** 500±20%  
**Rated Freq. Range (Hz)** 1-20000  
**Sound Pressure Level (dB)** 80±3  
**Magnet (g)** 5  
**Operating Temperature (°C)** -10~+40



Y0008-1




**Type** Y0009-11  
**Rated Impedance (Ω)** 8±20%  
**Rated (Max.) Power (W)** 0.15(0.3)  
**Resonance Frequency (Hz)** 500±20%  
**Rated Freq. Range (Hz)** 1-20000  
**Sound Pressure Level (dB)** 81±2  
**Magnet (g)** 0.6  
**Operating Temperature (°C)** -10~+40



Y0009-11



**Type** Y0009-12  
**Rated Impedance (Ω)** 32±15%  
**Rated (Max.) Power (W)** 0.2 (0.4)  
**Resonance Frequency (Hz)** 600±20%  
**Rated Freq. Range (Hz)** 1-20000  
**Sound Pressure Level (dB)** 83±3  
**Magnet (g)** 1.1  
**Operating Temperature (°C)** -10~+40



Y0009-12







# MYLAR SPEAKER




Type	<b>YDB06-12A</b>
Rated Impedance ( $\Omega$ )	8 $\pm$ 15%
Rated (Max.) Power (W)	0.25 (0.1)
Resonance Frequency (Hz)	500 $\pm$ 20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	80 $\pm$ 3
Magnet (g)	1.1
Operating Temperature ( $^{\circ}$ C)	-10 $\rightarrow$ +40




Type	<b>YDB06-13C</b>
Rated Impedance ( $\Omega$ )	8 $\pm$ 15%
Rated (Max.) Power (W)	0.25 (0.1)
Resonance Frequency (Hz)	450 $\pm$ 20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	80 $\pm$ 3
Magnet (g)	1.1
Operating Temperature ( $^{\circ}$ C)	-40 $\rightarrow$ +60



Type	<b>YDB06-14</b>
Rated Impedance ( $\Omega$ )	8 $\pm$ 15%
Rated (Max.) Power (W)	0.2 (0.1)
Resonance Frequency (Hz)	500 $\pm$ 20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	80 $\pm$ 3
Magnet (g)	1.1
Operating Temperature ( $^{\circ}$ C)	-10 $\rightarrow$ +40




Type	<b>YDB40-1</b>
Rated Impedance ( $\Omega$ )	30 $\pm$ 15%
Rated (Max.) Power (W)	0.15 (0.1)
Resonance Frequency (Hz)	400 $\pm$ 20%
Rated Freq. Range (Hz)	1-2000
Sound Pressure Level (dB)	85 $\pm$ 3
Magnet (g)	5
Operating Temperature ( $^{\circ}$ C)	-10 $\rightarrow$ +40




# MYLAR SPEAKER




<b>Type</b>	<b>YDB48-11</b>
Rated Impedance ( $\Omega$ )	16 $\pm$ 15%
Rated (Max.) Power (W)	0.18 (0.3)
Resonance Frequency (Hz)	400 $\pm$ 20%
Rated Freq. Range (Hz)	1-3500
Sound Pressure Level (dB)	80 $\pm$ 3
Magnet (g)	0.6
Operating Temperature ( $^{\circ}$ C)	-10-+40




<b>Type</b>	<b>YDB48-12</b>
Rated Impedance ( $\Omega$ )	28 $\pm$ 15%
Rated (Max.) Power (W)	0.2 (0.3)
Resonance Frequency (Hz)	550 $\pm$ 20%
Rated Freq. Range (Hz)	1-3500
Sound Pressure Level (dB)	80 $\pm$ 3
Magnet (g)	0.6
Operating Temperature ( $^{\circ}$ C)	-10-+40



<b>Type</b>	<b>YDB48-13</b>
Rated Impedance ( $\Omega$ )	8 $\pm$ 15%
Rated (Max.) Power (W)	0.18 (0.3)
Resonance Frequency (Hz)	550 $\pm$ 20%
Rated Freq. Range (Hz)	1-3500
Sound Pressure Level (dB)	80 $\pm$ 3
Magnet (g)	0.6
Operating Temperature ( $^{\circ}$ C)	-10-+40




<b>Type</b>	<b>YDB48-14</b>
Rated Impedance ( $\Omega$ )	8 $\pm$ 15%
Rated (Max.) Power (W)	0.2 (0.3)
Resonance Frequency (Hz)	550 $\pm$ 20%
Rated Freq. Range (Hz)	1-3500
Sound Pressure Level (dB)	82 $\pm$ 3
Magnet (g)	0.6
Operating Temperature ( $^{\circ}$ C)	-10-+40




# MYLAR SPEAKER




<b>Type</b>	<b>Y0820-1P</b>
Rated Impedance ( $\Omega$ )	8±20%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	600±20%
Rated Freq. Range (Hz)	1-3200
Sound Pressure Level (dB)	75±2
Magnet (g)	3.7
Operating Temperature (°C)	-10~+40




<b>Type</b>	<b>Y082508</b>
Rated Impedance ( $\Omega$ )	8±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	1000±20%
Rated Freq. Range (Hz)	1-3200
Sound Pressure Level (dB)	75±2
Magnet (g)	1.7
Operating Temperature (°C)	-40~+65



<b>Type</b>	<b>Y082508A</b>
Rated Impedance ( $\Omega$ )	8±15%
Rated (Max.) Power (W)	0.1 (0.2)
Resonance Frequency (Hz)	800±20%
Rated Freq. Range (Hz)	1-3200
Sound Pressure Level (dB)	75±2
Magnet (g)	1.7
Operating Temperature (°C)	-40~+65



<b>Type</b>	<b>Y082608</b>
Rated Impedance ( $\Omega$ )	8±10%
Rated (Max.) Power (W)	0.25 (0.5)
Resonance Frequency (Hz)	450±10%
Rated Freq. Range (Hz)	1-5000
Sound Pressure Level (dB)	85±2
Magnet (g)	1.1
Operating Temperature (°C)	-40~+90




# MYLAR SPEAKER




**Type**  
 Rated Impedance (Ω)  
 Rated (Max.) Power (W)  
 Resonance Frequency (Hz)  
 Rated Freq. Range (Hz)  
 Sound Pressure Level (dB)  
 Magnet (g)  
 Operating Temperature (°C)

**YDR3008**  
 8±15%  
 0.25 (0.5)  
 500±20%  
 1-2000  
 89±3  
 1.1  
 -40-+85



**Type**  
 Rated Impedance (Ω)  
 Rated (Max.) Power (W)  
 Resonance Frequency (Hz)  
 Rated Freq. Range (Hz)  
 Sound Pressure Level (dB)  
 Magnet (g)  
 Operating Temperature (°C)

**YDS4208**  
 8±15%  
 0.25 (0.5)  
 500±20%  
 1-2000  
 89±3  
 1.1  
 -40-+85



**Type**  
 Rated Impedance (Ω)  
 Rated (Max.) Power (W)  
 Resonance Frequency (Hz)  
 Rated Freq. Range (Hz)  
 Sound Pressure Level (dB)  
 Magnet (g)  
 Operating Temperature (°C)

**YDS68-11P**  
 8±15%  
 0.2 (0.4)  
 350±20%  
 180-2000  
 89±3  
 1.1  
 -10-+85

